

Fulvia gearbox layout **818-302**
 Fulvia 1,3 S **818-630**

Homologation 3020/5/4E

Tyres Toyo R888
 diameter circumference
 574 1.803 mm

bevel 4,78

gearbox		ratio	engine rev/min	output shaft	driveshaft rev/min	tyre diameter	mm/min	Km/h
output shaft	1,33							
gear 1	2,06	2,750	1000,00 7000,00	363,64 2545,45	76,11 532,77	1.803,00 1.803,00	137.226 960.584	8,2 57,64
gear 2	1,53	2,035	1000,00 7000,00	491,38 3439,66	102,85 719,93	1.803,00 1.803,00	185.433 1.298.030	11,1 77,88
gear 3	1,17	1,565	1000,00 7000,00	638,89 4472,22	133,72 936,05	1.803,00 1.803,00	241.099 1.687.692	14,5 101,26
gear 4	0,93	1,235	1000,00 7000,00	810,00 5670,00	169,53 1186,74	1.803,00 1.803,00	305.671 2.139.700	18,3 128,38
gear 5	0,75	1,000	1000,00 7000,00	1000,00 7000,00	209,30 1465,12	1.803,00 1.803,00	377.372 2.641.605	22,6 158,50

revs/min	gear 1	gear 2	gear 3	gear 4	gear 5
0	0	0	0	0	0
1000	8	11	14	18	23
7000	58	78	101	128	158

